

PLC-XU56 | PLC-XU51 | PLC-SU51

Brilliant Ideas for Your Business.

SANYO

- Brightness: 2,500 ANSI lumens (PLC-XU56), 2,000 ANSI lumens (PLC-XU51/SU51)
- XGA Resolution (PLC-XU56/51) or S-VGA Resolution (PLC-SU51)
- Automatic horizontal and vertical trapezoid adjustment
- Network integration and WLAN solutions (optional)
- DVI Input, Monitor Output
- 3-years guarantee



PLC-XU56 | PLC-XU51 | PLC-SU51

Brilliant Ideas for Your Business.



TECHNICAL DETAILS	PLC-XU56	PLC-XU51	PLC-SU51
Category	Business & Education		
Panel	3 x 0.8" TFT p-Si		
Lamp	200 W UHP		
Brightness ANSI lumens	2,500	2,000	2,000
Lamp Service Life	1,000 Hours / 2,000 Hours (Eco)		1,500 Hours / 2,000 Hours (Eco)
Standard Lens	F = 1.7 – 2.5 / f = 20 – 30 mm		
Aspect Ratio	1.2 – 1.9 : 1		
Distance (Standard Lens)	1.0 – 7.7 m (please use the three-dimensional distance calculator at www.sanyo.de)		
Contrast Ratio	450 : 1 (Auto Mode)		
Resolution in pixels	1,024 x 768 (XGA)		800 x 600 (S-VGA)
Horizontal Resolution	650 TV lines		
Uniformity	85 %		
Bandwidth / Frequency	140 MHz, horizontal 15 ~ 100 kHz, vertical 50 ~ 100 Hz		
Color Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N		
Connections	Input 1: DVI-I (digital/HDCP/analog), Audio: 1 x 3.5 mm Stereo Jack Input 2: D-Sub15 (RGB/Components/SCART-RGB) or monitor output Audio: shared with Input 2 Input 3: 1x Cinch (Composite), Audio: 2x Cinch (R/L-mono) Input 4: Mini-DIN 4-pin (S-Video), Audio: shared with Input 3 Audio Output: 3.5 mm Stereo Jack (variabel) Control Input 1: Mini-DIN 8-pin (RS232) Control Input 2: USB Typ B (mouse control)		
Audio	1 W Mono		
Keystone Correction	vertical +/- 40°; horizontal +/- 20°		
Lens-Shift	Fix U/D Ratio 9 : 1		
HDTV Signals	720p / 1,035i / 1,080i (HDTV-compatible)		
Computer Compatibility	S-XGA / XGA / S-VGA / VGA / Mac		XGA / S-VGA / VGA / Mac
Zoom / Focus	1.5x / manual		
Power Consumption	260 W / 100 – 240 V		
Warranty	3 Years Warranty		
Dimensions (W x H x D) in mm	298 x 71 x 218		
Weight	2.8 kg		
Standard Accessories	IR remote control with laser pointer and mouse function, batteries, operating manual, DVI/D-Sub15-cable, mouse cable for USB-Input, lens cover with fastener and cord, power cable, carrying bag		
Optional Accessories	Components/D-Sub15-cable, Multi Card Imager (with W-LAN-Card or CompactFlash-Card or LAN-Card), DVI-cable, SCART/D-Sub15-cable, Mac/VGA-Adapter		

For more information about optional accessories, please see the "Network Solutions and Accessories" brochure.



Technical specifications are subject to change without notice. Status 02/2005

